


CRD Series

10mm Coded Rotary DIP Switches



Description

The CRD series 10mm Coded Rotary DIP Switches is process sealed to withstand soldering and cleaning, making them perfect for use in harsh environments. CRD switches are used in address switching applications, data storage devices computer and peripherals and instrumentation and have a compact size to save space – in fact, they're 36% smaller than traditional 10mm DIP switches.

Features & Benefits

- Process sealed – withstands soldering and cleaning
- Thru-hole and surface mount models
- Crisp, positive detent ensures actuation
- RoHS compliant
- IP65

Specifications

Contact Rating	0.4 V AC, DC 20 V max.
-----------------------	------------------------

Mechanical and Electrical Characteristics

Electrical Life	20,000 steps min. @ 5 V DC 10 mA
Mechanical Life	30,000 steps min.
Contact Resistance	100 milliohms max. Initial @ 2 V DC 10mA
Insulation Resistance	1000 megohms min. @ 100 V DC
Dielectric Strength	300 V AC for 1 minute.
Operating Force	1000 grams max.

Environmental Characteristics

Operating Temperature	-20°C to 85°C
Storage Temperature	-40°C to 85°C

Process

Packaging	Switches supplied in anti-static tubes in full quantities only. This may affect order quantity. Surface mount models with MO actuators available in tape and reel, 500 pieces per reel.
------------------	---

Applications

- Address switching applications
- Data storage devices
- Computer and peripherals
- Instrumentation

Materials

Cover	PPS (Black)
Housing	
Actuator	PA 6T M0 actuator option; PBT L1 and W1 actuator option.
Contacts	Beryllium Copper with Gold over Nickel plate
Terminals	Brass with Gold Nickel plate

Note: Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.


CRD Series

10mm Coded Rotary DIP Switches



Ordering Number


The Build-A Switch concept allows you to mix and match options to create the switch you need. Below is a complete listing of options shown in catalog. To order, simply select desired option from each category and place in the appropriate box.




Note:
 1. L1 & W1 actuators are not available for switch functions CRD10R and CRD10C. L1 & W1 actuators are available for terminations A & C and switch functions CRD16R & CRD16C.

Switches with Standard Options

PC Mount (in mm)




Part #	No. Pos.	Quantity per Tube
CRD10RM0CB	10	45
CRD16RM0CB	16	45



Right Angle Mount (in mm)



Part #	No. Pos.	Quantity per Tube
CRD10RM0AB	10	45
CRD16RM0AB	16	45




CRD Series

10mm Coded Rotary DIP Switches



Surface Mount (mm)



Part #	No. Pos.	Quantity per Tube
CRD10RM0SB	10	45
CRD16RM0SB	16	45

Switch Function (mm)


CRD10R - 10 Position, BCD Actuator Color: Red

POS.	0	1	2	3	4	5	6	7	8	9
C	●	●	●	●	●	●	●	●	●	●
1		●								
2			●							
4				●	●	●	●			
8								●	●	●

Switches ship and to be solder processed in position "0"

CRD10C - 10 Position, BCD Compliment Actuator Color: Orange

POS.	0	1	2	3	4	5	6	7	8	9
C	●	●	●	●	●	●	●	●	●	●
1		●								●
2			●							●
4				●	●	●	●			●
8								●	●	●



Switches ship and to be solder processed in position "7"


CRD16R - 16 Position, Hexadecimal Actuator Color: Black

POS.	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
C	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
1		●		●		●		●		●		●		●		●
2			●		●		●		●		●		●		●	
4				●	●	●	●			●	●	●	●			●
8								●	●	●	●	●	●	●	●	●

Switches ship and to be solder processed in position "0"

CRD16C - 16 Position, Hexadecimal Complement Actuator Color: White



POS.	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
C	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
1	●		●		●		●		●		●		●		●	
2	●			●			●		●			●		●		●
4	●				●	●	●			●	●	●			●	●
8	●							●	●	●	●	●	●	●	●	●





Switches ship and to be solder processed in position "F"

Actuator inches (mm)


M0 (STD.) Flush with Screwdriver Slot



L1' Extended with Screwdriver Slot



W1' Wheel



Notes: Designed for #0 Phillips screwdriver.
 1: L1 & W1 actuators are not available for switch functions CRD10R and CRD10C. L1 & W1 actuators are available for terminations A & C and switch functions CRD16R & CRD16C.


CRD Series

10mm Coded Rotary DIP Switches




Terminations inches (mm)


C PC, Thru-hole



A Right Angle, PC Thru-hole



S Surface Mount




Contact Material

Option Code	RoHS Compliant ¹	RoHS Compatible ¹	Contact Material	Terminal Plating	Rating
B	Yes	Yes	Gold	Gold	Low Level / Dry Circuit 0.4 VC max. @ 20 V AC or DC max.

Note: See Technical Data section of this catalog for RoHS compliant and compatible definitions and specifications.

Tape and Reel inches (mm)



Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at <http://www.littelfuse.com/disclaimer-electronics>.